



AUTO-15HS • AUTO-15HSV

AUTOMATIC HORIZONTAL BANDSAW

Features

- Motorized roller feeding system
- Adjustable hydraulic feed rate provides an infinite range of cutting pressure
- Preset cut-piece counter with automatic stop
- Work height selector
- Out of stock switch with automatic stop
- Carbide guides for 1" wide blade
- Blade breakage detector with automatic stop
- Built-in coolant system distributed through blade guides
- Wire blade brush
- Built-in halogen work light



SPECIFICATIONS

ITEMS		MODEL	AUTO-15HS	AUTO-15HSV
CAPACITY	Round Minimum		15" (380 mm) 1.50" (38 mm)	
	Square Minimum		11" (280 mm) 1" (25 mm)	
	Rectangular Minimum		6" x 16" (150 x 410 mm) 1" x 1" (25 x 25 mm)	
	Max. material length stop setting		27" (685 mm)	
SAW BLADE	Speed		47, 80, 95, 127, 158, 250 fpm	Variable Speed 47 ~ 250 fpm
	Size		168" x 1" (4265 x 25 mm)	
	Tension		Manual	
	Guides		Carbide guides	
	Cleaning		Wire brush & flood coolant	
POWER	Blade		3 HP 3 Phase	
	Hydraulic		1/4 HP	
	Coolant pump		1/8 HP	
WORK FEEDING			Motorized roller feeding	
VISE			Manual	
WEIGHT & DIMENSIONS	Dimensions (L x W x H)		90" x 40" x 58"	
	Gross weight		2,420 lb. (1100 kg)	

• Specifications are subject to change without notice for further design improvements.



Adjustable material stop



Motorized roller feeding system

STANDARD MACHINE ACCESSORIES

- | | | |
|-----------------------------|-------------------------------|----------------------|
| 1. Adjustable material stop | 2. Complete coolant system | 3. Saw blade – 1 pc. |
| 4. Wire brush – 1 pc. | 5. Tool kits with box – 1 set | |

OPTIONAL MACHINE ACCESSORIES

- | | | |
|-----------------------|------------------------------------|--------------------------|
| 1. Roller table stand | 2. Infinitely variable blade speed | 3. Additional wire brush |
|-----------------------|------------------------------------|--------------------------|



MACHINERY SOLUTIONS, INC.

For more information please call: (310) 537-2522

web-site: www.VictorMachines.com e-mail: info@VictorMachines.com